

SAFETY JOGGER
INDUSTRIAL

Light

CADOR S1P MID

CADORMID

Durable S1P Safety Shoes For Multiple Industries

CADOR SP1 MID safety shoe with steel toe cap, piercingresistant midsole, slip resistance, ESD protection and customizable comfort for long shifts.

Upper	Mesh
Lining	3D-Mesh
Footbed	SJ Recycled Foam Footbed (96% recycled)
Midsole	Steel
Outsole	PU/PU
Toecap	Steel
Category	S1 P / SR, FO, ESD
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
Sample weight	0.609 kg
Norms	ASTM F2413:2018 EN ISO 20345:2022

CO_2 8.77 kg




GRY



S1P
You work in dry environments, no risk of water/liquid sprays, and you need protection for your toes, protection against perforation, and a good breathability? Then you need S1P safety footwear.



Electrostatic Discharge (ESD)
ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



Airblaze technology
Moisture and temperature management system to provide optimum wearer comfort by keeping your feet dry and comfortable.



Steel toecap
Robust metal support to protect the feet of the wearer against falling or rolling objects.



Steel midsole
Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.



Removable insole
Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.

Industries:
Assembly, Automotive, Food & beverages, Industry, Logistics

Environments:
Dry environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

Test results:

	Description	EN ISO 20345	Result	Measure unit
Upper	**Mesh**			
	Upper: permeability to water vapor	≥ 0.8	3.9	mg/cm^2 /h
	Upper: water vapor coefficient	≥ 15	41	mg/cm^2
Lining	**3D-Mesh**			
	Lining: permeability to water vapor	≥ 2	61.1	mg/cm^2 /h
	Lining: water vapor coefficient	≥ 20	490	mg/cm^2
Footbed	**SJ Recycled Foam Footbed (96% recycled)**			
	Footbed: abrasion resistance (dry/wet) (cycles)	25600/12800	25600/12800	cycles
Outsole	**PU/PU**			
	Outsole abrasion resistance (volume loss)	≤ 150	59	mm^3
	Outsole slip resistance SRA: heel	≥ 0.28	0.30	friction
	Outsole slip resistance SRA: flat	≥ 0.32	0.39	friction
	Outsole slip resistance SRB: heel	≥ 0.13	0.15	friction
	Outsole slip resistance SRB: flat	≥ 0.18	0.24	friction
	Antistatic value	0.1 - 1000	8.1	MegaOhm
	ESD value	0.1 - 100	73	MegaOhm
	Heel energy absorption	≥ 20	24	J
Toecap	**Steel**			
	Impact resistance toecap (clearance after impact 100J)	N/A	N/A	mm
	Compression resistance toecap (clearance after compression 10kN)	N/A	N/A	mm
	Impact resistance toecap (clearance after impact 200J)	≥ 14	15.0	mm
	Compression resistance toecap (clearance after compression 15kN)	≥ 14	19.0	mm

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Carbon footprint:

	Description	Result	Measure unit
CO2 emission			
	Material	6.49	kg
	Packing	0.13	kg
	Manufacturing	1.90	kg
	Transport	0.26	kg
		8.77 kg CO2/pair	

	Description	Result
Recycled content		
	Product	6%
	Packing	99%

CO2 calculation:
Values are rounded to two decimals.
These analyses are performed using our in-house environmental calculators, developed within the Cortina Group. The CO2 values are valid at the time of calculation and may be subject to change.