

SAFETY JOGGER INDUSTRIAL

Light

DOLCE S3

Slip-Resistant Safety Shoes for the Food Industry

DOLCE safety shoes with HACCP compliance, slip resistance and antistatic design deliver comfort, safety and durability across demanding work environments.

CO_2 10.39 kg

Upper	Nappa Action Leather
Lining	Recycled Mesh (100% recycled)
Footbed	SJ Recycled Foam Footbed (96% recycled)
Midsole	Steel
Outsole	PU/PU
Toecap	Steel
Category	S3 / SR, FO, CI
Size range	EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 JPN 21.5-31 / KOR 230-310
Sample weight	0.625 kg
Norms	EN ISO 20345:2022+A1:2024 ASTM F2413:2024



217



S3
S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.



SRA slip resistance
Slip resistance is one of the most important features of safety and occupational footwear. SRA slip resistant soles are tested on a ceramic tile with dilute soap solution.



Oil & fuel resistant
The outsole is resistant against oil and fuel.



Antistatic
Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm



Water resistant Upper (WRU)
Prevents penetration of water if not permanently exposed to high levels.



Heel energy absorption
Heel energy absorption reduces the impact of jumps or running on the body of the wearer.

Industries:
Automotive, Catering, Construction, Food & beverages, Logistics, Industry

Environments:
Dry environment, Wet environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

Test results:

	Description	EN ISO 20345	Result	Measure unit
Upper	**Nappa Action Leather**			
	Upper: permeability to water vapor	≥ 0.8	2.66	mg/cm^2 /h
	Upper: water vapor coefficient	≥ 15	24	mg/cm^2
Lining	**Recycled Mesh (100% recycled)**			
	Lining: permeability to water vapor	≥ 2	86.31	mg/cm^2 /h
	Lining: water vapor coefficient	≥ 20	691	mg/cm^2
Footbed	**SJ Recycled Foam Footbed (96% recycled)**			
	Footbed: abrasion resistance (dry/wet) (cycles)	25600/12800	25600/12800	cycles
Outsole	**PU/PU**			
	Outsole abrasion resistance (volume loss)	≤ 150	32	mm^3
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	≥ 0.31	0.41	friction
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	≥ 0.36	0.38	friction
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	≥ 0.19	0.27	friction
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	≥ 0.22	0.26	friction
	Antistatic value	0.1 - 1000	330.1	MegaOhm
	ESD value	0.1 - 100	N/A	MegaOhm
	Heel energy absorption	≥ 20	25	J
Toecap	**Steel**			
	Impact resistance toecap (clearance after impact 100J)	N/A	N/A	mm
	Compression resistance toecap (clearance after compression 10kN)	N/A	N/A	mm
	Impact resistance toecap (clearance after impact 200J)	≥ 14	15	mm
	Compression resistance toecap (clearance after compression 15kN)	≥ 14	19	mm

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Carbon footprint:

	Description	Result	Measure unit
CO2 emission			
	Material	8.04	kg
	Packing	0.19	kg
	Manufacturing	1.90	kg
	Transport	0.26	kg
		10.39 kg CO2/pair	

	Description	Result
Recycled content		
	Product	7%
	Packing	16%

CO2 calculation:
Values are rounded to two decimals.
These analyses are performed using our in-house environmental calculators, developed within the Cortina Group. The CO2 values are valid at the time of calculation and may be subject to change.