

SAFETY JOGGER
PROFESSIONAL

Light

DOMINIQUE 01

Stylish Sneakers with Advanced Shock Absorption Technology

DOMINIQUE is a trendy, shock-absorbing sneaker with air cushioning, slip-resistant grip, and breathable comfort for everyday performance.

Upper	Action Leather, Textile
Lining	Recycled 3D-Mesh (100% recycled)
Footbed	SJ Recycled Foam Footbed (96% recycled)
Outsole	PU/Rubber (NBR)
Category	01 / SR, FO, HRO, ESD
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
Sample weight	0.400 kg
Norms	EN ISO 20347:2022+A1:2024 ASTM F2892:2024

CO_2 7.57 kg



BLK



Oxygrip / SJ Grip
Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.



Electrostatic Discharge (ESD)
ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



SJ Foam
Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.



SRC slip resistance
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



Breathable upper
Increased moisture and temperature management for extended wearer comfort.

Industries:
Catering, Cleaning, Food & beverages, Medical

Environments:
Extreme slippery surfaces, Uneven surfaces

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

Test results:

	Description	EN ISO 20347	Result	Measure unit
Upper	**Action Leather, Textile**			
	Upper: permeability to water vapor	≥ 0.8	21.1	mg/cm^2 /h
	Upper: water vapor coefficient	≥ 15	21.6	mg/cm^2
Lining	**Recycled 3D-Mesh (100% recycled)**			
	Lining: permeability to water vapor	≥ 2	42.7	mg/cm^2 /h
	Lining: water vapor coefficient	≥ 20	342.3	mg/cm^2
Footbed	**SJ Recycled Foam Footbed (96% recycled)**			
	Footbed: abrasion resistance (dry/wet) (cycles)	25600/12800	25600/12800	cycles
Outsole	**PU/Rubber (NBR)**			
	Outsole abrasion resistance (volume loss)	≤ 150	81	mm^3
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	≥ 0.31	0.38	friction
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	≥ 0.36	0.39	friction
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	≥ 0.19	0.29	friction
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	≥ 0.22	0.32	friction
	Antistatic value	0.1 - 1000	97.4	MegaOhm
	ESD value	0.1 - 100	73.6	MegaOhm
	Heel energy absorption	≥ 20	37	J

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Carbon footprint:

	Description	Result	Measure unit
CO2 emission			
	Material	5.32	kg
	Packing	0.10	kg
	Manufacturing	1.90	kg
	Transport	0.26	kg
		7.57 kg CO2/pair	

	Description	Result
Recycled content		
	Product	12%
	Packing	99%

CO2 calculation:
Values are rounded to two decimals.
These analyses are performed using our in-house environmental calculators, developed within the Cortina Group. The CO2 values are valid at the time of calculation and may be subject to change.