SAFETY JOGGER
INDUSTRIAL



Medium

FLUX S3S LOW

FLUXS3SLOW

Lightweight comfortable and metal-free S3S low-cut

The FLUX S3S LOW is a low-cut safety shoe with a synthetic nubuck upper for water resistance and durability. Features a nanocarbon toecap, metal-free puncture-resistant midsole, and PU cleated outsole for strong grip on dry, wet, and slippery surfaces. The recycled mesh lining enhances breathability.

Upper	TPU, Synthetic Nubuck
Lining	Recycled Mesh (100% recycled)
Footbed	SJ Recycled Memory Foam Footbed (90% recycled)
Midsole	Anti-Puncture Textile
Outsole	PU/PU
Toecap	Nano Carbon
Category	S3S / SR, SC, FO, CI, ESD
Size range	EU 35-50 / UK 3.0-14.0 / US 3.0-15.0 JPN 21.5-33.0 / KOR 230-330
Sample weight	0.552 kg
Norms	EN ISO 20345:2022+A1:2024 ASTM F2413:2024

CO_2 8.37 kg



BLK

WPA · ESD 350Ω · CI · 3FIT SYSTEM · NESKRID



Metal free
Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



Slip resistance (SR)
Replaces the previously used term of SRA+SRB=SRC. SR means the slip test has been executed on tiles contaminated with soap and with oil.



Electrostatic Discharge (ESD)
ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



Breathable upper
Increased moisture and temperature management for extended wearer comfort.



Scuff Cap (SC)
Separately tested material to cover the toe cap area to reduce abrasion of the upper material (e.g. during kneeling operations) and extend usability of the safety shoe.



Nano carbon toecap
Ultralight high-tech material, metalfree with no thermal or electrical conductivity.

Industries:
Automotive, Industry, Assembly, Logistics, Food & beverages, Cleaning, Catering

Environments:
Dry environment, Extreme slippery surfaces, Wet environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

Test results:

	Description	EN ISO 20345	Result	Measure unit
Upper	**TPU, Synthetic Nubuck**			
	Upper: permeability to water vapor	≥ 0.8	2.3	mg/cm^2 /h
	Upper: water vapor coefficient	≥ 15	19.9	mg/cm^2
Lining	**Recycled Mesh (100% recycled)**			
	Lining: permeability to water vapor	≥ 2	49.8	mg/cm^2 /h
	Lining: water vapor coefficient	≥ 20	398.8	mg/cm^2
Footbed	**SJ Recycled Memory Foam Footbed (90% recycled)**			
	Footbed: abrasion resistance (dry/wet) (cycles)	25600/12800	Dry 25600 cycles/Wet 12800 cycles	cycles
Outsole	**PU/PU**			
	Outsole abrasion resistance (volume loss)	≤ 150	40.9	mm^3
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	≥ 0.31	0.49	friction
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	≥ 0.36	0.48	friction
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	≥ 0.19	0.30	friction
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	≥ 0.22	0.25	friction
	Antistatic value	0.1 - 1000	18.7	MegaOhm
	ESD value	0.1 - 100	5.2	MegaOhm
	Heel energy absorption	≥ 20	30	J
Toecap	**Nano Carbon**			
	Impact resistance toecap (clearance after impact 100J)	N/A	N/A	mm
	Compression resistance toecap (clearance after compression 10kN)	N/A	N/A	mm
	Impact resistance toecap (clearance after impact 200J)	≥ 14	15.5	mm
	Compression resistance toecap (clearance after compression 15kN)	≥ 14	21.5	mm

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Carbon footprint:

	Description	Result	Measure unit
CO2 emission			
	Material	6.09	kg
	Packing	0.12	kg
	Manufacturing	1.90	kg
	Transport	0.26	kg
		8.37 kg CO2/pair	

	Description	Result
Recycled content		
	Product	10%
	Packing	99%

CO2 calculation:
Values are rounded to two decimals.
These analyses are performed using our in-house environmental calculators, developed within the Cortina Group. The CO2 values are valid at the time of calculation and may be subject to change.