SAFETY JOGGER
INDUSTRIAL



Heavy

GA22 AGRI BOOT HIGH OB

GA22

PVC Waterproof Work Boots High

Durable PVC boots with slip-resistant outsole and waterproof protection. Ideal for agriculture, gardening or food processing.

Upper	SJ PVC
Lining	Tricot
Footbed	N/A
Outsole	PVC
Category	OB / SR
Size range	EU 37-48 / UK 4.0-13.0 / US 4.5-13.5 JPN 23-31.5 / KOR 240-315
Sample weight	0.770 kg
Norms	EN ISO 20347:2022+A1:2024





BLK


CO_2
6.45 kg



Slip resistance (SR)
Replaces the previously used term of SRA+SRB=SRC. SR means the slip test has been executed on tiles contaminated with soap and with oil.



Waterproof (WR)
Waterproof footwear prevents liquids to enter into the shoe.



Metal free
Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.

Industries:
Industry, Chemical, Cleaning, Food & beverages

Environments:
Muddy environment, Wet environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

Test results:

	Description	EN ISO 20347	Result	Measure unit
Upper	**SJ PVC**			
	Upper: permeability to water vapor	≥ 0.8	NA	mg/cm^2 /h
	Upper: water vapor coefficient	≥ 15	NA	mg/cm^2
Lining	**Tricot**			
	Lining: permeability to water vapor	≥ 2	NA	mg/cm^2 /h
	Lining: water vapor coefficient	≥ 20	NA	mg/cm^2
Footbed	**N/A**			
	Footbed: abrasion resistance (dry/wet) (cycles)	25600/12800	NA	cycles
Outsole	**PVC**			
	Outsole abrasion resistance (volume loss)	≤ 150	139	mm^3
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	≥ 0.31	0.36	friction
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	≥ 0.36	0.37	friction
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	≥ 0.19	0.23	friction
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	≥ 0.22	0.26	friction
	Antistatic value	0.1 - 1000	NA	MegaOhm
	ESD value	0.1 - 100	NA	MegaOhm
	Heel energy absorption	≥ 20	NA	J

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Carbon footprint:

	Description	Result	Measure unit
CO2 emission			
	Material	4.27	kg
	Packing	0.03	kg
	Manufacturing	1.90	kg
	Transport	0.26	kg
		6.45 kg CO2/pair	

	Description	Result
Recycled content		
	Product	0%
	Packing	99%

CO2 calculation:
Values are rounded to two decimals.
These analyses are performed using our in-house environmental calculators, developed within the Cortina Group. The CO2 values are valid at the time of calculation and may be subject to change.