SAFETY JOGGER PROFESSIONAL



Light

HENNY OB

Men's Fashionable Sneakers

HENNY work shoes combine grip, support, and breathable comfort for safe performance in food, cleaning, and medical industries.

Upper	Action Leather
Lining	Recycled Mesh (100% recycled)
Footbed	SJ Recycled Foam Footbed (96% recycled)
Outsole	TPR
Category	OB / E
Size range	EU 36-47 / UK 3.5-12.0 / US 4.0-13.0 JPN 22.5-31 / KOR 235-310
Sample weight	0.420 kg
Norms	EN ISO 20347:2022(Europe)

CE · OXYGRIP · NESKRID

CO_2 7.63 kg



LGR



NAV



Coolmax® lining
Coolmax® technology was originally developed for athletes. The material transports moisture and sweat, so that the body stays dry. We found it extremely suitable for people who work hard for hours every day too.

Industries:
Cleaning, Food & beverages, Medical

Environments:
Dry environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

Test results:

	Description	EN ISO 20347	Result	Measure unit
Upper	**Action Leather**			
	Upper: permeability to water vapor	≥ 0.8	1.1	mg/cm^2 /h
	Upper: water vapor coefficient	≥ 15	16.8	mg/cm^2
Lining	**Recycled Mesh (100% recycled)**			
	Lining: permeability to water vapor	≥ 2	51	mg/cm^2 /h
	Lining: water vapor coefficient	≥ 20	408.7	mg/cm^2
Footbed	**SJ Recycled Foam Footbed (96% recycled)**			
	Footbed: abrasion resistance (dry/wet) (cycles)	25600/12800	25600/12800	cycles
Outsole	**TPR**			
	Outsole abrasion resistance (volume loss)	≤ 150	145	mm^3
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	≥ 0.31	0.35	friction
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	≥ 0.36	0.39	friction
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	≥ 0.19	N/A	friction
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	≥ 0.22	N/A	friction
	Antistatic value	0.1 - 1000	N/A	MegaOhm
	ESD value	0.1 - 100	N/A	MegaOhm
	Heel energy absorption	≥ 20	24	J

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Carbon footprint:

	Description	Result	Measure unit
CO2 emission			
	Material	5.37	kg
	Packing	0.10	kg
	Manufacturing	1.90	kg
	Transport	0.26	kg
		7.63 kg CO2/pair	

	Description	Result
Recycled content		
	Product	12%
	Packing	99%

CO2 calculation:
Values are rounded to two decimals.
These analyses are performed using our in-house environmental calculators, developed within the Cortina Group. The CO2 values are valid at the time of calculation and may be subject to change.