SAFETY JOGGER
PROFESSIONAL



Light

# JULINE OB

JULINE2

**Stylish Work Pump**

The stylish JULINE work pumps offer superior comfort, excellent grip, and body posture relief. Perfect for uniform and catering industries.

| | |
|---|---|
| Upper | Lorica |
| Lining | Synthetic Leather |
| Footbed | SJ Recycled Foam Footbed (96% recycled) |
| Outsole | Rubber (NBR) |
| Category | OB / SR, FO, HRO, E |
| Size range | EU 35-42 / UK 3.0-8.0 / US 5.5-10.5<br>JPN 21.5-26.5 / KOR 230-270 |
| Sample weight | 0.270 kg |
| Norms | EN ISO 20347:2022+A1:2024<br>ASTM F3445:2024 |

$CO_2$ 4.48 kg



BLK



**Oxygrip / SJ Grip**
Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.




**SRA slip resistance**
Slip resistance is one of the most important features of safety and occupational footwear. SRA slip resistant soles are tested on a ceramic tile with dilute soap solution.



**Breathable upper**
Increased moisture and temperature management for extended wearer comfort.



**SJ Foam**
Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.



**Rubber outsole**
Rubber outsoles provide versatile functions that make them suitable for many areas of application: excellent cut resistance, heat and cold resistance, high flexibility at cold temperatures, resistance against oil, fuel and many chemicals.



**Heel energy absorption**
Heel energy absorption reduces the impact of jumps or running on the body of the wearer.

## Industries:
Catering, Uniform

## Environments:
Dry environment, Extreme slippery surfaces

## Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

## Test results:

| | Description | EN ISO 20347 | Result | Measure unit |
|---|---|---|---|---|
| **Upper** | **Lorica** | | | |
| | Upper: permeability to water vapor | ≥ 0.8 | 1.8 | mg/$cm^2$ /h |
| | Upper: water vapor coefficient | ≥ 15 | 17.3 | mg/$cm^2$ |
| **Lining** | **Synthetic Leather** | | | |
| | Lining: permeability to water vapor | ≥ 2 | 86.31 | mg/$cm^2$ /h |
| | Lining: water vapor coefficient | ≥ 20 | 691 | mg/$cm^2$ |
| **Footbed** | **SJ Recycled Foam Footbed (96% recycled)** | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | 25600/12800 | 25600/12800 | cycles |
| **Outsole** | **Rubber (NBR)** | | | |
| | Outsole abrasion resistance (volume loss) | ≤ 150 | 89 | $mm^3$ |
| | Basic Slip resistance - Ceramic + NaLS - Forward heel slip | ≥ 0.31 | 0.36 | friction |
| | Basic Slip resistance - Ceramic + NaLS - Backward forepart slip | ≥ 0.36 | 0.37 | friction |
| | SR Slip resistance - Ceramic + glycerin - Forward heel slip | ≥ 0.19 | 0.25 | friction |
| | SR Slip resistance - Ceramic + glycerin - Backward forepart slip | ≥ 0.22 | 0.28 | friction |
| | Antistatic value | 0.1 - 1000 | N/A | MegaOhm |
| | ESD value | 0.1 - 100 | N/A | MegaOhm |
| | Heel energy absorption | ≥ 20 | 50 | J |

Sample size: 37

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

## Carbon footprint:

| | Description | Result | Measure unit |
|---|---|---|---|
| **CO2 emission** | | | |
| | Material | 2.22 | kg |
| | Packing | 0.10 | kg |
| | Manufacturing | 1.90 | kg |
| | Transport | 0.26 | kg |
| | | **4.48 kg CO2/pair** | |

| | Description | Result |
|---|---|---|
| **Recycled content** | | |
| | Product | 9% |
| | Packing | 99% |

CO2 calculation:
Values are rounded to two decimals.
These analyses are performed using our in-house environmental calculators, developed within the Cortina Group. The CO2 values are valid at the time of calculation and may be subject to change.