SAFETY JOGGER
PROFESSIONAL



Light

JUNO 01 TLS

JUNO01TLS

Fashionable Sneaker With TLS Closure

JUNO occupational lightweight sneakers with climateoptimized comfort, heel energy absorption, antistatic grip and washable outsole.

Upper	3D-Mesh
Lining	Recycled Mesh (100% recycled)
Footbed	SJ Recycled Foam Footbed (96% recycled)
Outsole	Phylon/Rubber (NBR)
Category	01 / SR, FO
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
Sample weight	0.260 kg
Norms	ASTM F2892:2018 EN ISO 20347:2022(Europe)

CO_2 4.17 kg



DGR



BLK




BLU



WHT



TLS (Twist Lock System)
Safety Jogger's innovative TLS closure allows you to quickly tighten and loosen your safety footwear with one hand and under any conditions, even when you are wearing safety gloves. TLS ensures a fast, safe and easy precision fit that offers enhanced comfort and enables you to perform at your best.



Breathable upper
Increased moisture and temperature management for extended wearer comfort.




Oxygrip / SJ Grip
Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.



SRC slip resistance
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



3D mesh
Three-dimensional produced distance mesh to provide increased moisture and temperature management.



Heel energy absorption
Heel energy absorption reduces the impact of jumps or running on the body of the wearer.

Industries:
Catering, Food & beverages, Medical, Uniform

Environments:
Dry environment, Extreme slippery surfaces

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

Test results:

	Description	EN ISO 20347	Result	Measure unit
Upper	**3D-Mesh**			
	Upper: permeability to water vapor	≥ 0.8	25.3	mg/cm^2 /h
	Upper: water vapor coefficient	≥ 15	204	mg/cm^2
Lining	**Recycled Mesh (100% recycled)**			
	Lining: permeability to water vapor	≥ 2	21.1	mg/cm^2 /h
	Lining: water vapor coefficient	≥ 20	169	mg/cm^2
Footbed	**SJ Recycled Foam Footbed (96% recycled)**			
	Footbed: abrasion resistance (dry/wet) (cycles)	25600/12800	25600/12800	cycles
Outsole	**Phylon/Rubber (NBR)**			
	Outsole abrasion resistance (volume loss)	≤ 150	90	mm^3
	Outsole slip resistance SRA: heel	≥ 0.28	0.42	friction
	Outsole slip resistance SRA: flat	≥ 0.32	0.41	friction
	Outsole slip resistance SRB: heel	≥ 0.13	0.18	friction
	Outsole slip resistance SRB: flat	≥ 0.18	0.23	friction
	Antistatic value	0.1 - 1000	30.5	MegaOhm
	ESD value	0.1 - 100	N/A	MegaOhm
	Heel energy absorption	≥ 20	30	J

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Carbon footprint:

	Description	Result	Measure unit
CO2 emission			
	Material	1.91	kg
	Packing	0.10	kg
	Manufacturing	1.90	kg
	Transport	0.26	kg
		4.17 kg CO2/pair	

	Description	Result
Recycled content		
	Product	17%
	Packing	99%

CO2 calculation:
Values are rounded to two decimals.
These analyses are performed using our in-house environmental calculators, developed within the Cortina Group. The CO2 values are valid at the time of calculation and may be subject to change.