

SAFETY JOGGER TACTICAL

Medium

MODULO DELTA 06 LOW

MDLODLTLOW

Waterproof Low Occupational Shoes

MODULO DELTA 06 LOW waterproof leather shoes give workers secure grip, slip & heat resistance, and lasting protection indoors and outdoors.

Upper	Milled Full-Grain Leather
Lining	Membrane, Recycled 3D-Mesh (100% recycled)
Footbed	SJ Recycled Foam Footbed (96% recycled)
Outsole	BASF PU/Rubber (NBR)
Category	06 / SR, SC, LG, FO, HI, HRO, CI, ESD
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
Sample weight	0.555 kg
Norms	EN ISO 20347:2022+A1:2024 ASTM F2892:2024





BLK

CO_2 9.32 kg



Breathable leather upper
Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



Heat resistant outsole (HRO)
The outsole resists high temperatures up to 300°C.



Metal free
Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



Waterproof (WR)
Waterproof footwear prevents liquids to enter into the shoe.



Electrostatic Discharge (ESD)
ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



Heel energy absorption
Heel energy absorption reduces the impact of jumps or running on the body of the wearer.

Industries:
Tactical, Uniform

Environments:
Extreme slippery surfaces, Wet environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

Test results:

	Description	EN ISO 20347	Result	Measure unit
Upper	**Milled Full-Grain Leather**			
	Upper: permeability to water vapor	≥ 0.8	2.71	mg/cm^2 /h
	Upper: water vapor coefficient	≥ 15	26	mg/cm^2
Lining	**Membrane, Recycled 3D-Mesh (100% recycled)**			
	Lining: permeability to water vapor	≥ 2	6.36	mg/cm^2 /h
	Lining: water vapor coefficient	≥ 20	51	mg/cm^2
Footbed	**SJ Recycled Foam Footbed (96% recycled)**			
	Footbed: abrasion resistance (dry/wet) (cycles)	25600/12800	Dry 25600 cycles/Wet 12800 cycles	cycles
Outsole	**BASF PU/Rubber (NBR)**			
	Outsole abrasion resistance (volume loss)	≤ 150	117	mm^3
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	≥ 0.31	0.44	friction
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	≥ 0.36	0.42	friction
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	≥ 0.19	0.29	friction
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	≥ 0.22	0.32	friction
	Antistatic value	0.1 - 1000	28.4	MegaOhm
	ESD value	0.1 - 100	33	MegaOhm
	Heel energy absorption	≥ 20	35	J

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Carbon footprint:

	Description	Result	Measure unit
CO2 emission			
	Material	6.98	kg
	Packing	0.19	kg
	Manufacturing	1.90	kg
	Transport	0.26	kg
		9.32 kg CO2/pair	

	Description	Result
Recycled content		
	Product	7%
	Packing	16%

CO2 calculation:
Values are rounded to two decimals.
These analyses are performed using our in-house environmental calculators, developed within the Cortina Group. The CO2 values are valid at the time of calculation and may be subject to change.