SAFETY JOGGER
INDUSTRIAL



Light

SONORA S1 P

Low-cut breathable suede safety shoe

The SONORA low-cut shoes are made with suede, are very breathable, and offer robust protection and comfort. Ideal for dry environments, they feature S1P standards, SR slip resistance, steel toecap and midsoles, antistatic properties and heel energy absorption.

CO_2 11.61 kg



135

Upper	Suede Leather
Lining	Recycled Mesh (100% recycled)
Footbed	SJ Recycled Foam Footbed (96% recycled)
Midsole	Steel
Outsole	PU/PU
Toecap	Steel
Category	S1 P / SR, FO
Size range	EU 36-47 / UK 3.5-12.0 / US 4.0-13.0 JPN 22.5-31 / KOR 235-310
Sample weight	0.635 kg
Norms	ASTM F2413:2018 EN ISO 20345:2022





S1P
You work in dry environments, no risk of water/liquid sprays, and you need protection for your toes, protection against perforation, and a good breathability? Then you need S1P safety footwear.



Steel toecap
Robust metal support to protect the feet of the wearer against falling or rolling objects.



Steel midsole
Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.



Antistatic
Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm



SRC slip resistance
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



Heel energy absorption
Heel energy absorption reduces the impact of jumps or running on the body of the wearer.

Industries:
Automotive, Construction, Logistics, Industry

Environments:
Dry environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

Test results:

	Description	EN ISO 20345	Result	Measure unit
Upper	**Suede Leather**			
	Upper: permeability to water vapor	≥ 0.8	6.9	mg/cm^2 /h
	Upper: water vapor coefficient	≥ 15	61.1	mg/cm^2
Lining	**Recycled Mesh (100% recycled)**			
	Lining: permeability to water vapor	≥ 2	86.9	mg/cm^2 /h
	Lining: water vapor coefficient	≥ 20	695.4	mg/cm^2
Footbed	**SJ Recycled Foam Footbed (96% recycled)**			
	Footbed: abrasion resistance (dry/wet) (cycles)	25600/12800	25600/12800	cycles
Outsole	**PU/PU**			
	Outsole abrasion resistance (volume loss)	≤ 150	32	mm^3
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	≥ 0.31	0.47	friction
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	≥ 0.36	0.44	friction
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	≥ 0.19	0.26	friction
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	≥ 0.22	0.29	friction
	Antistatic value	0.1 - 1000	116.5	MegaOhm
	ESD value	0.1 - 100	N/A	MegaOhm
	Heel energy absorption	≥ 20	30	J
Toecap	**Steel**			
	Impact resistance toecap (clearance after impact 100J)	N/A	N/A	mm
	Compression resistance toecap (clearance after compression 10kN)	N/A	N/A	mm
	Impact resistance toecap (clearance after impact 200J)	≥ 14	17.0	mm
	Compression resistance toecap (clearance after compression 15kN)	≥ 14	21.5	mm

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Carbon footprint:

	Description	Result	Measure unit
CO2 emission			
	Material	9.34	kg
	Packing	0.12	kg
	Manufacturing	1.90	kg
	Transport	0.26	kg
		11.61 kg CO2/pair	

	Description	Result
Recycled content		
	Product	7%
	Packing	99%

CO2 calculation:
Values are rounded to two decimals.
These analyses are performed using our in-house environmental calculators, developed within the Cortina Group. The CO2 values are valid at the time of calculation and may be subject to change.