SAFETY JOGGER
INDUSTRIAL



ALLFLEXDOT 12PACK 4131A

ALLFLEXDOP

Precision Gloves 12Pack

ECO ALLFLEXDOT gloves with 87% recycled nylon liner, foam nitrile coating and grip dots for excellent dexterity and precise handling in dry conditions.

Liner	15 Gauge Polyamide/Elastane
Coating	Foam Nitrile/ Nitrile Dots
Category	TSF-Touchscreen function, SIF-Silicone Free
Size range	EU 6-12
Sample weight	0.021 kg
Norms	EN ISO 21420:2020 EN 388:2016 : 4 1 3 1 A

CE · ANSI /ISEA · 15G · DMF FREE PU · LATEX FREE · SILICONE FREE

EN ISO 21420

EN 388:2016

4131A



BLK

Industries:

Assembly, Automotive, Chemical, Cleaning, Construction, Industry, Logistics, Mining, Oil & Gas, Tactical

Performance level

EN388:2016	0	1	2	3	4	5
a. Abrasion resistance (cycles)	< 100	100	500	2000	8000	-
b. Cut resistance (Coup test)	< 1.2	1.2	2.5	5.0	10.0	20.0
c. Tear resistance (newton)	< 10	10	25	50	75	-
d. Puncture resistance (newton)	< 20	20	60	100	150	-

EN ISO 13997 (TDM-100 test)	A	B	C	D	E	F
e. Straight blade cut resistance (TDM 100 test)	2	5	10	15	22	30

a. Abrasion resistance: based on the number of cycles required to rub through the sample glove.
b. Cut resistance: based on the number of cycles required to cut through the sample at a constant speed with a rotating blade.
c. Tear resistance: based on the amount of force required to tear the sample.
d. Puncture resistance: based on the amount of force required to pierce the sample with a standard sized point.
e. Cut resistance according TDM100 test based on the number of cycles required to cut through the sample at a constant speed with a sliding blade.

Touchscreen compatible
You can use your smartphone or tablet without taking off the gloves, thanks to their special coating.

DMF-free PU
Made from polyurethane that doesn't contain DMF (a chemical that can be harmful), which means they are safe to use.