

EASY MAX

EASYMAX

Extra-Wide Non-Slip Overshoes

EASY MAX overshoes with SR slip-resistant soles and Tiger Grip® traction for wet, greasy surfaces. Waterproof, durable, and fully autoclavable.

CO_2 3.37 kg



GRY

Upper	Rubber (NBR)
Lining	N/A
Footbed	N/A
Midsole	N/A
Outsole	Rubber (NBR)
Toecap	N/A
Category	SR, FO
Size range	EU S35-37-Y46-48
Sample weight	0.200 kg
Norms	CTC Expert statement according to the CTC CE C 002_c evaluat
Certificates	UKCA Certificate (UK Conformity Assessed) For Footwear CTC Expert statement according to the CTC CE C 002_c evaluat DCTU OVERSHOE (Ukraine)



Tiger Grip Technology
Outsoles with Tiger Grip technology are renowned for their slip resistance, ability to withstand wear and tear and excellent traction on different surfaces, even wet and uneven ones. They are crafted with an exclusive rubber compound and engineered with specific patterns and grooves to enhance grip and stability.



Autoclavable
Can be sterilized in an autoclave.



Slip resistance (SR)
Replaces the previously used term of SRA+SRB=SRC. SR means the slip test has been executed on tiles contaminated with soap and with oil.

Industries:
Cleaning, Chemical, Food & beverages, Medical

Environments:
Extreme slippery surfaces, Snowy and icy

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

Test results:

	Description		Result	Measure unit
Outsole	**Rubber (NBR)**			
	Outsole abrasion resistance (volume loss)	≤ 150	144	mm^3
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	≥ 0.31	0.55	friction
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	≥ 0.36	0.53	friction
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	≥ 0.19	0.38	friction
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	≥ 0.22	0.37	friction
	Antistatic value	0.1 - 1000	372	MegaOhm
	ESD value	0.1 - 100	N/A	MegaOhm
	Heel energy absorption	≥ 20	N/A	J
Toecap	**N/A**			
	Impact resistance toecap (clearance after impact 100J)	N/A	N/A	mm
	Compression resistance toecap (clearance after compression 10kN)	N/A	N/A	mm
	Impact resistance toecap (clearance after impact 200J)	N/A	N/A	mm
	Compression resistance toecap (clearance after compression 15kN)	N/A	N/A	mm

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Carbon footprint:

	Description	Result	Measure unit
CO2 emission			
	Material	1.13	kg
	Packing	0.08	kg
	Manufacturing	1.90	kg
	Transport	0.26	kg
		3.37 kg CO2/pair	

	Description	Result
Recycled content		
	Product	0%
	Packing	100%

CO2 calculation:
Values are rounded to two decimals.
These analyses are performed using our in-house environmental calculators, developed within the Cortina Group. The CO2 values are valid at the time of calculation and may be subject to change.

Size guide:

Sizes	S			M			L		XL			XXL		
EU	35	36	37	38	39	40	41	42	43	44	45	46	47	48
UK	3	3,5	4	5	6	6,5	7	8	9	10	10,5	11	12	13
US Woman	5,5	6	6,5	7,5	8	9	9,5	10,5	10,5+					
US Men				5,5	6,5	7,5	8	9	10	10,5	11,5	12	13	13,5
JPN	21,5	22,5	23	24	25	25,5	26	26,5	27	28	29	30	31	31,5
KOR	230	235	240	250	255	260	265	270	280	285	295	300	310	315