

VISITOR

Safety Overshoes With Aluminium Toe

- With velcro strap
- Can be adapted to all kinds of footwear
- Color code to identify sizes
- Size range: S(34-38) - M(39-43) - L(44-48)

CO_2 6.97 kg



BLK

Upper	Rubber (NBR)
Lining	N/A
Footbed	N/A
Midsole	N/A
Outsole	Rubber (NBR)
Toecap	Aluminium
Category	SR, FO
Size range	EU S34-38-X44-48
Sample weight	0.310 kg
Norms	CTC Expert statement according to the CTC CE C 002_c evaluat
Certificates	UKCA Certificate (UK Conformity Assessed) For Footwear CTC Expert statement according to the CTC CE C 002_c evaluat DCTU OVERSHOE (Ukraine)



Tiger Grip Technology
Outsoles with Tiger Grip technology are renowned for their slip resistance, ability to withstand wear and tear and excellent traction on different surfaces, even wet and uneven ones. They are crafted with an exclusive rubber compound and engineered with specific patterns and grooves to enhance grip and stability.




Aluminum toecap
Aluminum toecaps bring the resistance of steel toes to a lighter weight (30-50% lighter than steel). Alloy toes have a low profile, which makes them ideal for sportive safety shoes. The average weight of the aluminum cap is about 50/60 gr.



Slip resistance (SR)
Replaces the previously used term of SRA+SRB=SRC. SR means the slip test has been executed on tiles contaminated with soap and with oil.



Oil & fuel resistant
The outsole is resistant against oil and fuel.



Rubber outsole
Rubber outsoles provide versatile functions that make them suitable for many areas of application: excellent cut resistance, heat and cold resistance, high flexibility at cold temperatures, resistance against oil, fuel and many chemicals.

Industries:
Logistics, Medical, Industry

Environments:
Extreme slippery surfaces, Snowy and icy

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

Test results:

	Description		Result	Measure unit
Outsole	**Rubber (NBR)**			
	Outsole abrasion resistance (volume loss)	≤ 150	140	mm^3
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	≥ 0.31	N/A	friction
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	≥ 0.36	0.47	friction
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	≥ 0.19	N/A	friction
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	≥ 0.22	0.23	friction
	Antistatic value	0.1 - 1000	N/A	MegaOhm
	ESD value	0.1 - 100	N/A	MegaOhm
	Heel energy absorption	≥ 20	N/A	J
Toecap	**Aluminium**			
	Impact resistance toecap (clearance after impact 100J)	N/A	N/A	mm
	Compression resistance toecap (clearance after compression 10kN)	N/A	N/A	mm
	Impact resistance toecap (clearance after impact 200J)	N/A	24.0	mm
	Compression resistance toecap (clearance after compression 15kN)	N/A	25.0	mm

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Carbon footprint:

	Description	Result	Measure unit
CO2 emission			
	Material	2.58	kg
	Packing	0.08	kg
	Manufacturing	3.80	kg
	Transport	0.51	kg
		6.97 kg CO2/pair	

	Description	Result
Recycled content		
	Product	0%
	Packing	100%

CO2 calculation:
Values are rounded to two decimals.
These analyses are performed using our in-house environmental calculators, developed within the Cortina Group. The CO2 values are valid at the time of calculation and may be subject to change.

Size guide:

Sizes	S					M					L				
EU	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48
UK	2,5	3	3,5	4	5	6	6,5	7	8	9	10	10,5	11	12	13
US Woman	4,5	5,5	6	6,5	7,5	8	9	9,5	10,5	10,5+					
US Men	2	3	4	4,5	5,5	6,5	7,5	8	9	10	10,5	11,5	12	13	13,5
JPN	21	21,5	22,5	23	24	25	25,5	26	26,5	27	28	29	30	31	31,5
KOR	225	230	235	240	250	255	260	265	270	280	285	295	300	310	315